



## SeaRox® FB 6020

SeaRox FB 6020 is a lightweight stone wool insulation slab (board). Reinforced aluminium foil (ALU) and glass cloth (GW200, GW400, GW-A, ALU-G) facings are available on request.

## **Application**

The slab (board) is suitable for fire-rated A-class steel constructions where low weight plays an important role, such as onboard passenger ships, naval ships and offshore supply vessels.



## **Product properties**

Product property	Performance		Norms
Thermal conductivity	T (°C) λ (W/mK)	10 0,034	EN 12667
Maximum service temperature	250°C		
Advised maximum surface temp. for facings	80°C		
Fire classification	Non-combustible Approved for A-class constructions Low flame spread properties (for facings)		IMO 2010 FTP Code
Nominal density	40 kg/m³		EN 1602
Water absorption (short term)	≤ 1 kg/m²		EN 1609 EN ISO 29767
Sound absorption (directly mounted)	Thickness: 70 mm unfaced $\alpha_{w} = 0.95$		ISO 354 Evaluated after ISO 11 654

## Compliance

- SeaRox FB 6020 complies with directive 2014/90/EU of 23 July on marine equipment (MED) and IMO 2010 FTP Code.
- Above product declarations are also applicable for product with optional facing.
- ROCKWOOL stone wool insulation is made from volcanic rock and complies with Note Q, regulation (EC) No. 1272/2008.





As ROCKWOOL has no control over insulation design and workmanship, accessory materials or applications conditions, ROCKWOOL does not warranty the performance or result of any installation containing ROCKWOOL products. ROCKWOOL's overall liability and the remedies available are limited by the general terms and conditions of sale. This warranty in lieu of all other warranties and conditions expressed or implied, including the warranties of merchantability and fitness for a particular purpose. ROCKWOOL Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.

Evaluated after ISO 11 654

ROCKWOOL® Technical Insulation, ROCKWOOL®, SeaRox® and ProRox® are registered trademarks of ROCKWOOL A/S and cannot be used without a prior written consent.

www.rti.rockwool.com