

TECHNICAL INSULATION

SeaRox[®] Glass Cloth Tape 120

SeaRox Glass Cloth Tape 120 is a white glass cloth composite self-adhesive tape, lined with siliconised paper.

Application

The tape is used to seal joints between SeaRox GW200 and GW-A faced stone wool products and when terminating at a metal surface.



Product properties

Product property	Performance	Norms
Weight	120 g/m²	
Colour	White	
Operating temperature	-20°C to + 110°C	
Fire classification	Low flame spread properties	IMO 2010 FTP Code

Installation

The surface must be clean, dry, and free of grease, oil and other contaminants.

Adequate pressure should be used when applying to any surface. The user must evaluate product suitability for any application.

Storage

12 months when stored out of direct sunlight at 21°C / 50% relative humidity.



As ROCKWOOL has no control over insulation design and workmanship, accessory materials or applications conditions, ROCKWOOL does not warranty the performance or result of any installation containing ROCKWOOL products. ROCKWOOL's overall liability and the remedies available are limited by the general terms and conditions of sale. This warranty in lieu of all other warranties and conditions expressed or implied, including the warranties of merchantability and fitness for a particular purpose. ROCKWOOL Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.

ROCKWOOL® Technical Insulation, ROCKWOOL®, SeaRox® and ProRox® are registered trademarks of ROCKWOOL A/S and cannot be used without a prior written consent.