

Safe Use Instruction Sheet – ProRox WM 962

Date of issue: 22.12.2022

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Trade name : ProRox WM 962, all variants.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended use : ProRox: Thermal insulation of industrial installations.

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Rockwool B.V.
Rockwool Technical Insulation
Industrieweg 15
6045 JH Roermond
Netherlands
T: +31 475 35 3915
www.rti.rockwool.com

Producing factory:

- Czech Republic (Bohumin)

1.4. Emergency telephone number

Emergency number : +31 475 35 3915
(business hours GMT+1)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified.

Adverse physicochemical, human health and environmental effects

No additional information available.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable.

2.3. Other hazards not contributing to the classification

Other hazards which do not result in classification : Dust can be generated during cutting or fabrication of the product. When heated to approximately 150-200°C for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate the eyes and respiratory system. Further information can be found in section 8.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Stone wool (1)	(EC-No.) 926-099-9	95 - 100	Not classified

(1) Man-made vitreous (silicate) fibres with random orientation with alkaline oxide and alkali earth oxide (Na₂O+K₂O+CaO+MgO+BaO) content greater than 18% by weight and fulfilling one of the note Q conditions.

Safety Use Instruction Sheet – ProRox WM 962
3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Biopolymeric binder		0 - 5	Not classified
Mineral oil		0.5	Not classified

SECTION 4: First aid measures
4.1. Description of first aid measures

First-aid measures general	: If exposure symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash with plenty of water and soap. Rinse skin with water/shower.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Call a physician
First-aid measures after ingestion	: Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact	: May cause physical irritation upon direct contact.
------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures
5.1. Extinguishing media

Suitable extinguishing media	: Water spray, carbon dioxide (CO ₂), dry chemical powder, foam.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: The product itself does not burn.
Explosion hazard	: Not explosive.

5.3. Advice for firefighters

Firefighting instructions	: Use self-contained breathing apparatus when in close proximity to fire. Wear proper protective equipment.
Protective equipment for firefighters	: Wear a self contained breathing apparatus. Wear recommended personal protective equipment.

SECTION 6: Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. Refer to chapter 8.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: In case of inadequate ventilation wear respiratory protection. Refer to chapter 8.
Emergency procedures	: Stop leak if safe to do so. Evacuate and limit access.

6.2. Environmental precautions

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Refer to sections 8 and 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Clean contaminated surface with vacuum or dampen with water spray prior to sweeping up. Place waste in appropriate containers for disposal.
-------------------------	---

6.4. Reference to other sections

Refer to sections 8 and 13.

SECTION 7: Handling and storage
7.1. Precautions for safe handling

Precautions for safe handling	: Unpack material at application site to avoid unnecessary handling of product. Keep work area clean. Collect all waste in suitable and labelled containers and dispose according to local legislation. Wet dust with water before sweeping. Ensure good ventilation.
-------------------------------	---

Safety Use Instruction Sheet – ProRox WM 962

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Store tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits : Comply with national and local regulations for dust exposure.

DNEL/PNEC : No CSR required for this article.

8.2. Exposure controls

Appropriate engineering controls:

Ensure adequate ventilation.

Eye protection:

Tightly fitting safety goggles (EN 166).

Skin and body protection:

Cover any exposed skin. Wear protective gloves.

Respiratory protection:

During handling: Use an approved mask with particle filter type P1 or better (EN 149) in case of dust formation or when airborne particulates are above exposure limits.

Hot equipment – operating at temperatures above 150-200°C (run in period):

During initial run-in, a thermal decomposition of organic matter can be observed starting around 150–200°C. This can be observed as a release of small amounts of potentially irritating and harmful fumes.

This does not affect the quality or declared performances of installed products.

The amount and composition of the fumes will depend on a number of variables including the amount of insulation installed, service temperature, temperature run in gradient, ventilation rate, jacketing materials.

The run-in period can last for a period from a few hours and up to several days. Ventilate the area well and keep a distance to the heated equipment.

For high concentrations in enclosed spaces use a supplied air respirator. For lower concentrations an approved mask with particle filter type P1 or better (EN 149) is adequate.

Selection of specific respirator type shall be made by a qualified person and all equipment should be appropriately fitted, used and maintained.

Special precautions advised when installing directly on hot surfaces.

Other information:

Handle in accordance with good industrial hygiene and safety procedures.



Ventilate working area if possible




Waste should be disposed of according to local regulations



Cover exposed skin.
When working in unventilated area wear disposable face mask



Clean area using vacuum equipment



Wear goggles when working overhead



Rinse in cold water before washing

The material also fulfil the labelling agreement that EURIMA has made with EC Commission.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Article. Stone wool
Colour	: Grey. Green
Odour	: Odourless
Odour threshold	: Not applicable
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: Not applicable
Melting point	: > 1000°C

Safety Use Instruction Sheet – ProRox WM 962

Freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: 150-200°C
Flammability (solid, gas)	: Not flammable
Vapour pressure	: Not applicable
Relative vapour density at 20 °C	: Not applicable
Relative density	: See product data sheet
Solubility	: Chemically inert substance Water: Insoluble in water
Log Pow	: Not applicable
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive
Oxidising properties	: Not applicable
Explosive limits	: Not explosive

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity
10.1. Reactivity

Hazardous polymerisation does not occur.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, bases.

10.6. Hazardous decomposition products

Heating Mineral Wool above 150-200°C can lead to a one time release of small amounts of fumes and gasses. Composition typical to thermal decomposition of organic compounds based on Carbon, Nitrogen and Hydrogen: Primarily Carbon oxides, with smaller amounts of e.g. Monoisocyanates, Nitric oxide, Acetaldehyde, Formaldehyde and Hydrogen cyanide. The organic binder applied in this product is optimised for reduced high temperature emissions, thereby reducing run in time.

SECTION 11: Toxicological information
11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified pH: Not applicable
Serious eye damage/irritation	: Not classified pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Additional information	: The mechanical effect of coarse fibres in contact with throat, skin or eyes may cause temporary itching/inconvenience

Safety Use Instruction Sheet – ProRox WM 962
SECTION 12: Ecological information
12.1. Toxicity

Ecology - general : This product is not hazardous

12.2. Persistence and degradability
ProRox WM 962

Persistence and degradability	Product is not easily biodegradable
-------------------------------	-------------------------------------

12.3. Bioaccumulative potential
ProRox WM 962

Bioaccumulative potential	No bioaccumulation
---------------------------	--------------------

12.4. Mobility in soil
ProRox WM 962

Ecology - soil	Not expected to adsorb on soil
----------------	--------------------------------

12.5. Results of PBT and vPvB assessment

No additional information available.

12.6. Other adverse effects

Other adverse effects : No information available

SECTION 13: Disposal considerations
13.1. Waste treatment methods

Product/Packaging disposal recommendations : Comply with local regulations for disposal.

Additional information : Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN-no.:	: Not applicable
14.2. UN proper shipping name	: Not applicable
14.3. Transport hazard class(es)	: Not applicable
14.4. Packing group	: Not applicable
14.5. Environmental hazards	: Not applicable
14.6. Special precautions for user	: None specified
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	: Not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The materials fulfil the directives:

2000/53/EC	: End-of life vehicles
850/2004/EC	: On persistent organic pollutants (including PFOS (perfluorooctane sulfonates) and pentabromodiphenyl ether)
1907/2006/EC, annex XVII	: Concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), (including octabromodiphenyl ether)
2011/65/EC	: On the restriction of the use of certain hazardous substances in electrical and electronic equipment (ROHS), including decaBDE.

15.2. Chemical safety assessment

No assessment required.

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CSR	Chemical Safety Report
DNEL	Derived No-Effect Level
EURIMA	European Insulation Manufacturers Association

Safety Use Instruction Sheet – ProRox WM 962

IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
Log Pow	Bioaccumulative potential
PBT	Persistent, Bioaccumulative, Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	very Persistent, very Bioaccumulative

Training advice:

No special training is required. However, the user should be well instructed in the execution of the task, and have normal training in the use of personal protective equipment.

Other information:

None

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.